



VHM-Spiralbohrer, 5xD, Z=2, äußere Kühlmittelzufuhr


Bestellnummer	D1(mm)	D2(mm)	L1(mm)	L2(mm)	L3(mm)	RG
ABO5D-3/6-23-66Z2	3.0	6.0	66.0	23.0	30.0	2
ABO5D-3.3/6-23-66Z2	3.3	6.0	66.0	23.0	30.0	2
ABO5D-3.5/6-23-66Z2	3.5	6.0	66.0	23.0	30.0	2
ABO5D-4/6-29-74Z2	4.0	6.0	74.0	29.0	38.0	2
ABO5D-4.2/6-29-74Z2	4.2	6.0	74.0	29.0	38.0	2
ABO5D-4.5/6-29-74Z2	4.5	6.0	74.0	29.0	38.0	2
ABO5D-5/6-35-82Z2	5.0	6.0	82.0	35.0	46.0	2
ABO5D-5.5/6-35-82Z2	5.5	6.0	82.0	35.0	46.0	2
ABO5D-6/6-35-82Z2	6.0	6.0	82.0	35.0	46.0	2
ABO5D-6.5/8-43-91Z2	6.5	8.0	91.0	43.0	55.0	2
ABO5D-6.8/8-43-91Z2	6.8	8.0	91.0	43.0	55.0	2
ABO5D-7/8-43-91Z2	7.0	8.0	91.0	43.0	55.0	2
ABO5D-7.5/8-43-91Z2	7.5	8.0	91.0	43.0	55.0	2
ABO5D-8/8-43-91Z2	8.0	8.0	91.0	43.0	55.0	2
ABO5D-8.5/10-49-103Z2	8.5	10.0	103.0	49.0	63.0	2
ABO5D-9/10-49-103Z2	9.0	10.0	103.0	49.0	63.0	2
ABO5D-9.5/10-49-103Z2	9.5	10.0	103.0	49.0	63.0	2
ABO5D-10/10-49-103Z2	10.0	10.0	103.0	49.0	63.0	2
ABO5D-10.2/12-56-118Z2	10.2	12.0	118.0	56.0	73.0	2
ABO5D-10.5/12-56-118Z2	10.5	12.0	118.0	56.0	73.0	2
ABO5D-11/12-56-118Z2	11.0	12.0	118.0	56.0	73.0	2
ABO5D-12/12-56-118Z2	12.0	12.0	118.0	56.0	73.0	2