


VHM-Micro-Schaftfräser, Z=2, mit Eckenradius, konischer Hals


Bestellnummer	Winkel	D1(mm)	D2(mm)	D3(mm)	D4(mm)	L1(mm)	L2(mm)	L3(mm)	ER(mm)	RG
SMEK1.5-1.4/6-15-60	1.4°	1.5	6.0	1.42	2.087	60.0	1.35	15.0	0.15	2
SMEK1.5-0.9/6-25-70	0.9°	1.5	6.0	1.42	2.163	70.0	1.35	25.0	0.15	2
SMEK1.5-1.9/6-15-60	1.9°	1.5	6.0	1.42	2.326	60.0	1.35	15.0	0.15	2
SMEK1.5-1.4/6-20-65	1.4°	1.5	6.0	1.42	2.332	65.0	1.35	20.0	0.15	2
SMEK1.5-1.9/6-20-65	1.9°	1.5	6.0	1.42	2.657	65.0	1.35	20.0	0.15	2
SMEK1.5-1.9/6-30-75	1.9°	1.5	6.0	1.42	3.321	75.0	1.35	30.0	0.15	2
SMEK2-0.9/6-30-70	0.9°	2.0	6.0	1.92	2.809	70.0	1.7	30.0	0.2	2
SMEK2-1.4/6-25-65	1.4°	2.0	6.0	1.92	3.059	65.0	1.7	25.0	0.2	2
SMEK2-0.9/6-40-80	0.9°	2.0	6.0	1.92	3.123	80.0	1.7	40.0	0.2	2
SMEK2-1.9/6-20-65	1.9°	2.0	6.0	1.92	3.134	65.0	1.7	20.0	0.2	2
SMEK2-1.4/6-30-70	1.4°	2.0	6.0	1.92	3.303	70.0	1.7	30.0	0.2	2
SMEK2-0.9/6-50-90	0.9°	2.0	6.0	1.92	3.438	90.0	1.7	50.0	0.2	2
SMEK2-1.4/6-35-75	1.4°	2.0	6.0	1.92	3.548	75.0	1.7	35.0	0.2	2
SMEK2-1.4/6-40-80	1.4°	2.0	6.0	1.92	3.792	80.0	1.7	40.0	0.2	2
SMEK2-1.9/6-30-70	1.9°	2.0	6.0	1.92	3.798	70.0	1.7	30.0	0.2	2
SMEK2-1.9/6-35-75	1.9°	2.0	6.0	1.92	4.129	75.0	1.7	35.0	0.2	2
SMEK2-1.9/6-40-80	1.9°	2.0	6.0	1.92	4.461	80.0	1.7	40.0	0.2	2
SMEK3-0.9/6-40-80	0.9°	3.0	6.0	2.86	4.038	80.0	2.5	40.0	0.3	2
SMEK3-0.9/6-50-90	0.9°	3.0	6.0	2.86	4.352	90.0	2.5	50.0	0.3	2
SMEK3-0.9/6-60-100	0.9°	3.0	6.0	2.86	4.667	100.0	2.5	60.0	0.3	2
SMEK3-1.9/6-30-70	1.9°	3.0	6.0	2.86	4.685	70.0	2.5	30.0	0.3	2
SMEK3-1.4/6-40-80	1.4°	3.0	6.0	2.86	4.693	80.0	2.5	40.0	0.3	2
SMEK3-1.4/6-50-90	1.4°	3.0	6.0	2.86	5.182	90.0	2.5	50.0	0.3	2
SMEK3-1.9/6-40-80	1.9°	3.0	6.0	2.86	5.348	80.0	2.5	40.0	0.3	2